



Adresse / Address

Datum / Date

Kontakt / Contact

March 2010

Ledermann GmbH & Co. KG
Willi-Ledermann-Str. 1
D-72160 Horb a.N.

Tel. +49 (0) 74 51 / 93-0
info@leuco.com
www.leuco.com

Betreff / Subject

„Manual trimming made easy“ - the new trimming saw blade by LEUCO

Seite / Page

01/02

Inhalt / Content

LEUCO now offers high quality trimming saw blades for manual feed on table saws.

Dividing cuts in solid woods and glued solid wood become very easy. This even more as the special tooth geometry and the small cutting width minimize the cutting pressure.

Thanks to the combination of lower power consumption and improved handling there is no alternative to the new trimming saw blade program by LEUCO for all those who want to make trimming cuts on their table saw in a flexible and universal way.

The cutting material specially designed for hard woods improves the cutting quality and guarantees longest edge lives.

Bildmaterial / Imagery



The new trimming saw blade by LEUCO with internal rakers

Machine / Application

- | table saws
- | length cutting saws
- | for dividing cuts in soft and hard woods as well as glued solid wood

Design

- | tooth configuration: alternate top bevel
- | cutting material: HL Solid 15, extremely high bending strength
- | special design with chip limiter and internal rakers

Advantages

- | high process stability thanks to low risk of sawing untrue and low danger of setback
- | exact and precise cuts need less rework
- | low cutting pressure for low energy consumption and high efficiency



No more problems with dividing cuts - even large cross cuts - in solid woods without danger of setback!

LEUCO

www.leuco.com



Adresse / Address

Datum / Date

Kontakt / Contact

March 2010

Ledermann GmbH & Co. KG
Willi-Ledermann-Str. 1
D-72160 Horb a.N.

Tel. +49 (0) 74 51 / 93-0
info@leuco.com
www.leuco.com

Betreff / Subject

Seite / Page

„Manual trimming made easy“ - the new trimming saw blade by LEUCO

02/02

Inhalt / Content

Dimensions

Ø D	B	b	Ø d	Ø dmax	max flange Ø	teeth	NL	HW grade	Ident-No.
350	3,5	2,45	30	70	140	24	2+2	2/7/42 + 2/9,5/46,5 + 2/10/60	189643
400	3,5	2,45	30	80	160	28	2+2	2/7/42 + 2/9,5/46,5 + 2/10/60	189644
450	4,2	2,8	30	80	160	36	2+2	2/7/42 + 2/9,5/46,5 + 2/10/60	189645
[mm]	[mm]	[mm]	[mm]	[mm]	[mm]		[St.]		

